

Cobra MARINE™

MARINE VHF TRANSCEIVER
ÉMETTEUR-RÉCEPTEUR VHF MARINE
RICETRASMITTENTE VHF MARINE
TRANSECTOR VHF MARINE
VHF MARINRADIO



INTERNATIONAL, U.S.A.
AND CANADA CHANNELS



INSTANT CHANNEL 16



SCAN



SUBMERSIBLE
MEETS JIS7 STANDARDS



UNIQUE FEATURE
FOR THE MR HH300 EU:

- Dual-Watch

ACTUAL SIZE

MRHH 300 EU

Feature	Benefit
1 or 5 Watts	Dual output power for short and long communication.
International, U.S.A. & Canada Channels	Allows operation on any of the three (3) different channel maps established for these areas.
Private Channels	Available for programming in country of purchase.
Instant Channel 16	Instant access to channel 16 for emergency situations.
Dual Watch	Monitors two (2) channels at once — Channel 16 and one (1) user selected channel.
Scan	Scan all channels to find conversations in progress.
Signal Strength Meter	Shows the strength of incoming signal.
Button/Key Lock	Locks function buttons/keys to eliminate accidental change of settings.
Battery Tray With Charge Contacts (one per transceiver)	Allows charging of batteries in unit.
Illuminated Function Keys	Allows high visibility of function keys.
Illuminated LCD Display: Large	Allows high visibility of display.
Submersible	Meets JIS7 standards; Submersible for 30 minutes in one meter deep water.
Included Accessories	
Swiveling Belt Clip	Secures the radio while on the go. Also removable.
Wrist Strap	For ease of carrying and securing while on the go.

Unit Specifications

General	
Number of Channels	All: International, U.S.A., Canadian
Channel Spacing	25 kHz
Modulation	5 kHz Max.
Input Voltage	7.2 VDC
Battery Life: 5:5:90 Stand-by	Alkaline Batteries 8 Hours @ 5 Watts, 10 Hours @ 1 Watt
Battery Requirements	6 AA alkaline batteries (not included)
Current Drain:	
Stand-by	40 mA
Receive	200 mA
Transmit	1.8 A @ High Power 700 mA @ Low Power
Temperature Range	-20°C to 50°C
Unit Dimensions	145 mm H x 68 mm W x 38.5 mm D Including antenna
Unit Weight (Lbs)	220 g Without batteries
Receiver	
Frequency Range	156.050 to 162.425 MHz
Receiver Type	Double Conversion Super-Heterodyne
Sensitivity:	
20 dB Quieting	0.35 µV
12 dB Sinad	0.30 µV
Adjacent Channel Selectivity	-60 dB
Intermodulation and Rejection	-60 dB
Spurious & Image Rejection	-60 dB
AF Output	250 mW @ 8 Ohms
Transmitter	
Frequency Range	156.025 to 162.425 MHz
RF Output Power	1 or 5 Watts
Spurious Emissions	-60 dB @ High Power -55 dB @ Low Power
Frequency Stability	+/-10 ppm
FM Hum & Noise	40 dB
Packaging Specifications	
Individual Clam/Box Dimensions	205 mm H x 175 mm W x 75 mm D
Individual Clam/Box Weight	438 g
Master Pack Qty.	4
Master Pack Dimensions	325 mm H x 217 mm W x 200 mm D
Master Pack Weight	2252 g
SKU #	MR HH300 EU
UPC #	0 28377 20076 2

Features and specifications subject to change.

NOTHING Comes Close to a Cobra®

Bergsala AB, tel: +46 (0)300-509 20, www.cobra-se.com

Nothing comes close to a Cobra® and the snake design are registered trademarks of Cobra Electronics Corporation, USA. Cobra Electronics Corporation™, CEEL™ and CobraMarine™ are trademarks of Cobra Electronics Corporation, USA.